

650 Watt Buffet System MB062-R

- Drop-in counter-top design, aluminum housing, heavy duty energy efficient electronics, high-impact commercial grade tempered glass
- Microprocessor monitors vital components 120 times per second to check for overheating, power supply problems, and more. Buffet unit shuts off and displays error codes enabling user to diagnose and correct minor problems
- Automatic pan detection allows for instant energy transmission to pan, and almost no energy consumption when pan is not present
- Maximum temperature limit prevents damage to chafing dishes and food spoilage and keeps operations within ventilation code
- Precise wireless temperature control. Units must be used with an induction compatible chafing dish fitted with CookTek® Magneeto™, or CookTek® RFID tagged chafing dishes
- Four standard temperature settings
- Eleven additional temperature settings can be accessed via simple keypad function
- Magneeto™ devices can be programmed from the unit enabling automatic temperature control
- Standard Cat 5e or Cat 6 patch cable from unit to control box is included (MUST BE SHIELDED).
- Easy to clean tempered glass top
- Lock feature prevents unwanted setting changes



"B" Model dropped into banquet box



"B" Model with control box

Model Number	MB062R
Power Requirements	200-240VAC, 1PH
Power consumption	650W (max rating)
Amperage	2.7 amps (maximum)
Power range	100 - 650 W
Dimensions (mm)	381 x 381 x 95.25H
Power cord length 6ft 182cm/ty	IEC 60320 C13
Remote control box cord length (m)	1.8