



Garnet Gastronom Cabinets

- 1 or 2 door cabinet accommodating 2/1GN shelves / containers.
- CoolSmart intelligent controller offering 15% energy savings, and enhanced performance.
- Energy efficient economy mode ensuring effective temperature control for excellent food safety.
- Improved defrost functionality for increased cabinet efficiency.
- CoolSmart controller designed for easy operation and features clear digital display and audible and visual alarms.
- Self closing doors with 140°C dwell with curved plastic module handle and easy to clean, replaceable magnetic gasket.
- 128mm heavy duty front / rear swivel and brake castors for mobility and positioning.
- 4 shelves fitted with as standard or 12 pairs of tray-slides per cabinet to accommodate 2/1 gastronorm containers.
- Environmental friendly 75mm GWP low foam injected insulation for excellent thermal efficiency
- Top mounted removable refrigeration system for easy service and maintenance.
- Designed for effective and efficient performance in 43°C ambient temperature
- Audio and visual HI/LO temperature alarm and door opening alarm.
- Condensor cleaning light to indicate when cleaning is required to ensure effective and efficient performance.
- Defrost water is vaporized using waste heat from the compressor.
- HACCP compliant.



Garnet Gastronorm Cabinets

Model	HG1TSA	LG1TSA	HG2TSA	LG2TSA
External dimensions (mm)				
Height	1965	1965	1965	1965
Width	737	737	1400	1400
Depth	824	824	824	824
Internal dimensions (mm)				
Height	1370	1370	1370	1370
Width	587	587	1174	1174
Depth	683	683	683	683
Door Opening Depth (mm)	1519	1519	1519	1519
Packed (mm)				
Height	2070	2070	2070	2070
Width	837	837	1500	1500
Depth	924	924	924	924
Weight: Add 5kg per product for packing	137 kg	137 kg	137 kg	142 kg
Power output: start up (amps) running	12.4 3	22.5 4	13.4 3.5	22.5 4.5
Energy consumption	3.6 kW in 24H	10.6 kW in 24H	5.8kW in 24H	3.6 kW in 24H