



Duo 2

- Double skinned cabinet.
- Simple Clear controls.
- Easy two touch operation.
- Standard fitted drain pump.
- Standard fitted break tank and rinse booster.
- WRAS (water regulation advisory scheme) approved air gap.
- 2 minute wash cycle and 480 glasses/hour.
- Supplied with 1 x glass rack.
- Integral chemical dosing pumps .
- Unique removable door and rack guides.
- Auto cleaning and drain down.
- Moulded steel interior wash chamber.
- Extremely low capacity wash tank.
- Full coverage filter System.

Options

-Start-up chemical from Mac Brothers, thereafter available from Spektank.



Width (mm)	470	Maximum racks per hour - water @50°C	30
Depth (mm)	550	Cycle times	2 min
Depth - door open (mm)	870	Water connection -BSP	G ¾"
Height (mm)	760	Water inlet height from floor level (mm)	40
Rack size (square) (mm)	400	Required water pressure (flow)	0.5 bar
Maximum pints per rack	16	Required water flow	8
Door opening height (mm)	330	Drain type	pumped
Maximum clear entry height (mm)	320	Drain size (mm)	22
Operating level	70 db	Wash pump capacity	220 Ltrs/min
Net weight	38 kg	Wash tank capacity	10 Ltrs
Amps required - I phase	15 amps	Wash tank operating temperature	55°C
Total Connected Load	2.75 kW	Rinse boiler capacity	6.5 Ltrs
Wash tank heating	2.0 kW	Rinse boiler operating temperature	65°C
Wash pump size	0.22 kW	Rinse water consumption - @ 2 Bar	2.25 Ltrs