



Duo H750 - Features

- Double skinned cabinet.
- Simple Clear controls.
- Easy two touch operation.
- Standard fitted drain pump.
- Standard fitted break tank and rinse booster.
- WRAS (water regulation advisory scheme) approved air gap.
- Supplied with 2 x glass racks.
- Integral chemical dosing pumps.
- Unique removable door and rack guides.
- Auto cleaning and drain down.
- Moulded steel interior wash chamber.
- Extremely low capacity wash tank.
- Full coverage filter System.
- Start-up chemicals supplied by Mac Brothers, there after available from Spectank.



Width (mm)	570	Cycle times	3½ min
Depth (mm)	630	Water connection - BSP	G ¾"
Depth - door open (mm)	990	Water inlet height from floor level (mm)	40
Height (mm)	835	Required water pressure (flow)	0-2 bar
Rack size (square) (mm)	500	Drain size (mm)	22
Door opening height (mm)	360	Wash pump size	0.74 kW
Maximum clear entry height (mm)	345	Wash pump capacity	380 Ltrs/min
Operating level	70 db	Wash tank capacity	18 Ltrs
Gross weight	70 kg	Wash tank operating temperature	55°C
Amps required - 1 phase	30 amps	Rinse boiler capacity	7.0 Ltrs
Amps required - 3 phase	16 amps	Rinse boiler operating temperature	85°C
-Water fed @ 40° C	16 amps	Rinse water consumption - @ 2 Bar	2.75 Ltrs
-Water fed @ 10° C	16 amps	Max/Min stand pipe height from floor (mm)	700/450
Total Connected Load	6.75 kW	Max/Min water pressure	6 bar/0.5 bar
Wash tank heating	2.0 kW	Minimum water flow	2.51/Ltrs
Maximum racks per hour - water @50°C	20		