

Refrigeration

Gastronorm Pizza Back Underbar Fridge

- HCFC free foam injected polyurethane insulation 40mm thick and 40mm on top.
- Self contained refrigeration with r134a refrigerant.
- Plain top or with splashback from 1.2mm grade 430 Stainless steel.
- Insulated Stainless steel doors with magnetic rubber gaskets and opening to take standard gastronorm inserts
- Standard on 100mm rubber castors.
- Digital temperature control.
- Compressor overload alarm with red error light on digital control.
- Compressor protected by high pressure / low pressure (HP/LP) switch to prolong refrigeration lifespan.



Model	Description	Weight	Volume	Power	Cooling	Dimensions
UB14GNP	2.5 Door pizza back gastronorm underbar	113 kg	350 L	1/4 HP	1440 BTU	1400 x 650 x 915H
UB18GNP	3.5 Door pizza back gastronorm underbar	156 kg	540 L	1/4 HP	1440 BTU	1800 x 650 x 915H
UB24GNP	4.5 Door pizza back gastronorm underbar	199 kg	780 L	1/3 HP	1810 BTU	2400 x 650 x 915H

Optional Extras

Model	Description
UBShelf	Fridge shelf
UBSlide	Sk5 / gastronorm Trayslide per door
UBBar18	Locking bar 1200/1400/1800
UBBar24	Locking bar 2400
UBBack12	Stainless steel back & louvre 1200
UBBack18	Stainless steel back & louvre 1800
UBBack24	Stainless steel back & louvre 2400
UBCut	Recessed cutting board 300mm deep
UBLock	Door locks
UBDwr2	Drawer set x 2 drawers
UBDwr3	Drawer set x 3 drawers
UBLight	Blue internal lights