

# Food Warming & Display Equipment

## Hot Pass - Standard

- Specify length and leg gap when ordering.
- Available up to 2400mm long.
- Passes are 300mm deep from 0.9mm thick with a 185mm gap from grade 430 Stainless steel.
- Legs from grade 304 Stainless steel 25mm square tubing with 300mm gap to bottom tier.
- Thermostatic temperature control 0 - 180°C.



Model	Description	Weight	Power	Dimensions
H1T1HL	Hot pass standard 1 tier, 1 hot, 300 leg per metre	6.5 kg/m	See Hot Pass rating on page C6	Specify length when ordering
H2T1HB	Hot pass standard 2 tier, 1 hot, no leg	12.9 kg/m		
H2T1HL	Hot pass standard 2 tier, 1 hot, 300 leg per metre	13.2 kg/m		
H2T2HL	Hot pass standard 2 tier, 2 hot, 300 leg per metre	16.3 kg/m		
H3T1HB	Hot pass standard 3 tier, 1 hot, no leg	17.1 kg/m		
H3T2HB	Hot pass standard 3 tier, 2 hot, no leg	18.3 kg/m		
H3T2HL	Hot pass standard 3 tier, 2 hot, 300 leg per metre	18.3 kg/m		
H3T3HL	Hot pass standard 3 tier, 3 hot, 300 leg per metre	19 kg/m		

## Cold Pass - Standard

- Specify length and leg gap when ordering.
- Available up to 2400mm long.
- Passes are 300mm deep from 0.9mm thick with a 185mm gap from grade 430 Stainless steel.
- Legs from grade 304 Stainless steel 25mm square tubing with 300mm gap to bottom tier.



Model	Description	Weight	Dimensions
C1TL	Cold pass standard 1 tier, 300 leg - per metre	5.8 kg/m	Specify length when ordering
C2TB	Cold pass standard 2 tier, no leg - per metre	10.5 kg/m	
C2TL	Cold pass standard 2 tier, 300 leg - per metre	10.8 kg/m	
C3TB	Cold pass standard 3 tier, no leg - per metre	15.5 kg/m	
C3TL	Cold pass standard 3 tier, 300 leg - per metre	15.8 kg/m	

## Hot Pass Rating

Lenght	1 Hot	2 Hot	3 Hot
600-1450	1000W	2000W	3000W
1500-1700	1500W	3000W	4500W
1750-2100	2000W	4000W	6000W (2 Leads) 3 phase
2150-2400	2500W	5000W (2 Leads)	7500W (2 Leads) 3 phase