



## Hydro H957 A - Features

- Simple, clear controls.
- Easy operation.
- Integral WRAS (water regulation advisory scheme) approved type A air gap with rinse booster.
- Folded steel interior wash chamber.
- Auto cycle start.
- Automatic self drain and clean down programme.
- Continuous hood cleaning system.
- Full coverage filter system.
- Self draining wash pump.
- In line or corner installation.
- Integral chemical dosing system with detergent pump.
- Supplied with start-up chemical from Mac Brothers, there after available from Spektank.
- Supplied with STD baskets.



Width (mm)	630	Maximum racks per hour	40/20
Depth (mm)	720	Cycle Times (mins)	1½ or 3
Height - hood open (mm)	1940	Water connection - BSP	G ¾"
Height - hood closed (mm)	1520	Required water pressure (flow)	0 -2 bar
Rack size (square) (mm)	500	Required water flow	6.6 Ltrs/min
Maximum clear entry height (mm)	385	Pump Drain (mm)	0-600
Operating noise level	70 db	Wash tank heating	4.35 kW
Net weight	130 kg	Rinse boiler heating	8.64 kW
Drain size (mm)	40	Wash pump capacity	380 Ltrs/min
Drain Pump	Standard	Wash tank capacity	39 Ltrs
Amps required - 3 phase		Wash tank operating temperature	55°C
Water fed @ 40° C	19 amps	Rinse boiler capacity	7 Ltrs
Water fed @ 10° C	19 amps	Rinse boiler operating	85°C
Total Connected Load	12.4 kW	Rinse water consumption - @ 2 Bar	3.5 Ltrs