

Refrigeration

Polar Top Underbar Fridge

- Foam injected top from grade 304 Stainless steel.
- Self contained refrigeration with r134a refrigerant.
- Insulated Stainless steel doors with magnetic rubber gasket.
- Standard on 100mm rubber castors.
- 1 x Epoxy coated adjustable shelf per large door
- Digital temperature control.
- Compressor overload alarm with red error light on digital control.
- Compressor protected by high pressure / low pressure (HP/LP) switch to prolong refrigeration lifespan.



Model	Description	Weight	Volume	Power	Cooling	Dimensions
UB18PT	2 Door polar top underbar	140 kg	470 L	3/8 HP	2220 BTU	1800 x 650 x 915H
UB24PT	3 Door polar top underbar	187 kg	660 L	1/2 HP	2220 BTU	2400 x 650 x 915H

Gastronorm Underbar Fridge

- HCFC free foam injected polyurethane insulation 40mm thick and 40mm on top.
- Self contained refrigeration with r134a refrigerant.
- Plain top or with splashback from 1.2mm grade 430 Stainless steel.
- Insulated Stainless steel doors with magnetic rubber gasket and opening to take standard gastronorm inserts
- Standard on 100mm rubber castors.
- Digital temperature control.
- Compressor overload alarm with red error light on digital control.
- Compressor protected by high pressure / low pressure (HP/LP) switch to prolong refrigeration lifespan.



Model	Description	Weight	Volume	Power	Cooling	Dimensions
UB14GN	2.5 Door gastronorm underbar	104 kg	350 L	1/4 HP	1440 BTU	1400 x 650 x 915H
UB18GN	3.5 Door gastronorm underbar	144 kg	540 L	1/4 HP	1440 BTU	1800 x 650 x 915H
UB24GN	4.5 Door gastronorm underbar	185 kg	780 L	1/3 HP	1810 BTU	2400 x 650 x 915H