

Refrigeration

Polar Wells & Salad Valleys

- Foam injected top from grade 304 Stainless steel.
- Standard well is 100mm deep.
- On ordering indicate if a drain from the well is required.
- Self contained refrigeration unit with r134a refrigerant.
- Freestanding on mild steel stand or drop-in (to be specified).
- Refrigeration must be ventilated.
- All polar wells are supplied fully refrigerated to ensure that they are in working order.



Model	Description	Power	Dimensions
SV2T1600	2 Tier salad valley 1600	3/8 HP	1600 x 650 or per spec
SV2T2000	2 Tier salad valley 2000	3/8 HP	2000 x 650 or per spec
SV2T2500	2 Tier salad valley 2500	3/8 HP	2500 x 650 or per spec
SV3T1600	3 Tier salad valley 1600	3/8 HP	1600 x 800 or per spec
SV3T2000	3 Tier salad valley 2000	3/8 HP	2000 x 800 or per spec
PW1200	Polar well 1200	1/3 HP	1200 x 650 or per spec
PW1600	Polar well 1600	3/8 HP	1600 x 650 or per spec
PW2200	Polar well 2200	3/8 HP	2200 x 650 or per spec

Optional Extras

- Curved or flat Sneeze Guards.
- Stainless steel cladding and louvre for stand.