

Refrigeration

Remote Glass Door Underbar Fridge

- HCFC free foam injected polyurethane insulation 40mm thick and 40mm on top.
- Remote refrigeration for 10m run with r134a refrigerant.
- Plain top or with splashback from 1.2mm grade 430 Stainless steel.
- Double Glazed Aluminum doors with removable magnetic rubber gasket.
- Standard on legs or batons.
- 2 x Epoxy coated adjustable shelf per large door.



Model	Description	Weight	Volume	Power	Cooling	Dimensions
UB12R	2 Glass door remote underbar	94 kg	470 L	1/4 HP	1440 BTU	1200 x 650 x 915H
UB18R	3 Glass door remote underbar	141 kg	660 L	1/3 HP	1810 BTU	1800 x 650 x 915H
UB24R	4 Glass door remote underbar	180 kg	850 L	3/8 HP	2220 BTU	2400 x 650 x 915H
UB28R	5 Glass door remote underbar	223 kg	1070 L	1/2 HP	3620 BTU	2800 x 650 x 915H

Pizza Back Underbar Fridge

- HCFC free foam injected polyurethane insulation 40mm thick and 40mm on top.
- Self contained refrigeration with r134a refrigerant.
- Plain top or with splashback from 1.2mm grade 430 Stainless steel.
- Insulated Stainless steel doors with magnetic rubber gasket.
- Standard on 100mm rubber castors.
- Digital temperature control.
- Compressor overload alarm with red error light on digital control.
- Compressor protected by high pressure / low pressure (HP/LP) switch to prolong refrigeration lifespan.



Model	Description	Weight	Volume	Power	Cooling	Dimensions
UB12P	1.5 Door pizza back underbar	84 kg	350 L	1/4 HP	1440 BTU	1200 x 650 x 915H
UB18P	2.5 Door pizza back underbar	126 kg	540 L	1/3 HP	1810 BTU	1800 x 650 x 915H
UB24P	3.5 Door pizza back underbar	162 kg	740 L	3/8 HP	2220 BTU	2400 x 650 x 915H
UB28P	4.5 Door pizza back underbar	200 kg	950 L	1/2 HP	3620 BTU	2800 x 650 x 915H