

# Refrigeration

## Standard Underbar Fridge

- HCFC free foam injected polyurethane insulation 40mm thick and 40mm on top.
- Self contained refrigeration with r134a refrigerant.
- Plain top or with splashback from 1.2mm grade 430 Stainless steel.
- Insulated Stainless steel doors with magnetic rubber gasket.
- Standard on 100mm rubber castors.
- Digital temperature control.
- Compressor overload alarm with red error light on digital control.
- Compressor protected by high pressure / low pressure (HP/LP) switch to prolong refrigeration lifespan.



Model	Description	Weight	Volume	Power	Cooling	Dimensions
UB12S	1.5 Door standard underbar	89 kg	350 L	1/4 HP	1440 BTU	1200 x 650 x 915H
UB18S	2.5 Door standard underbar	134 kg	540 L	1/4 HP	1440 BTU	1800 x 650 x 915H
UB24S	3.5 Door standard underbar	171kg	740 L	1/3 HP	1810 BTU	2400 x 650 x 915H
UB28S	4.5 Door standard underbar	212 kg	950 L	3/8 HP	2880 BTU	2800 x 650 x 915H

## Glass Door Underbar Fridge

- HCFC free foam injected polyurethane insulation 40mm thick and 40mm on top.
- Self contained refrigeration with r134a refrigerant.
- Plain top or with splashback from 1.2mm grade 430 Stainless steel.
- Insulated Stainless steel doors with magnetic rubber gasket.
- Standard on 100mm rubber castors.
- Digital temperature control.
- Compressor overload alarm with red error light on digital control.
- Compressor protected by high pressure / low pressure (HP/LP) switch to prolong refrigeration lifespan.



Model	Description	Weight	Volume	Power	Cooling	Dimensions
UB12G	1.5 Glass door standard underbar	104 kg	350 L	1/4 HP	1440 BTU	1200 x 650 x 915H
UB18G	2.5 Glass door standard underbar	144 kg	540 L	1/3 HP	1810 BTU	1800 x 650 x 915H
UB24G	3.5 Glass door standard underbar	184 kg	740 L	3/8 HP	2220 BTU	2400 x 650 x 915H
UB28G	4.5 Glass door standard underbar	228 kg	950 L	1/2 HP	3620 BTU	2800 x 650 x 915H